

*patent pending technology

ST2000 Short Throw

Flame

Advantages:

Efficiency: 2X more power efficient than comparable fixtures, FCD/watt

Light Weight: 50% lighter than

comparable fixtures

Compact: 2X smaller than comparable

fixtures

Power supply: Integrated & power

factor corrected

Xenon lamp: Integrated reflector and lamp for Safe installation, removal

and disposal

5500-5700 Kelvin: color temperature,

consistent lamp to lamp



Features:

Variable output, Operates at 700-900W without changing the lamp

Integrated under belly mount high efficiency power factor corrected power supply

Internal mount 6 frame color changer

Separate front and rear lens action with ¼ turn lock for easy focus and zoom

Dowser/fader, chopper and iris for special effects

Pan and tilt with locking tilt

Elapsed time meter

Integrated quartz free lamp and reflector allow easy lamp adjustment too tune the output

Lighter, Brighter, Leaner & Greener!

A New Followspot By:



Introducing a revolutionary New followspot. The Brite Box, Inc. " Flame" Short Throw

Developed by Brite Box, Inc. Manufactured by Phoebus MFG

Brite Box Short Throw					
Model		ST2000			
Length		40"			
Width	Including handles	17"			
Height	Including color changer and PS	24"			
Fixture weight	Less stand	105 lbs			
Stand weight		55 lbs			
Power Requirements	Single phase, 50/60HZ	200 - 245 V A/C			
Current	Max.	13 amperes A/C			
Wattage	Max.	900			
Road case dimension	Includes fixture, stand and power supply	70" x 39" by 23"			
Road case weight	Includes fixture, stand and power supply	218lbs			

Brite Box Short Throw Flame Photometrics						
Data Sheet 900W						
Throw ft'	75	100	150	200	250	
Spot						
Footcandles	683	384	171	96	61	
maximum dia. '	6.9	9.2	13.8	18.4	23.0	
minimum dia.'	1.4	1.9	2.8	3.8	4.7	
Flood						
Footcandles	157	88	39	22	14	
Maximum dia.'	14.4	19.2	28.8	38.4	48.0	

^{*}All photometrics were measured at 900W, with 70% field uniformity

^{*} Depending on individual systems, photometrics can vary by 10% from above values



www.briteboxinc.com

Contact Arc Light Efx, Inc.